



# S5

## 952051651

S5-5-C60-32  
TUBULAR SENSORS

## OVERVIEW

- Wide versatility of optic functions and connections
- High operating distances for all functions
- Models with trimmer adjustment and stability LED
- Rugged and impermeable plastic housing

## TECHNICAL FEATURES

### Detection properties

Nominal sensing distance	600mm
--------------------------	-------

Sensitivity adjustment	Trimmer
------------------------	---------

### Application

Function Principle	Diffuse beam
--------------------	--------------

Description	Tubular M18 - axial optic
-------------	---------------------------

Functions	Diffuse beam
-----------	--------------

#### Outputs

Output type	NPN/PNP - Dark/Light sel. L/D
Output Function	L/D
Response time	1

#### Electrical data

Operating Voltage	10...30VDC
No-Load supply current	$\leq 30\text{mA}$
Load current	$\leq 100\text{mA}$
Output voltage drop	$\leq 2,5\text{V}@I_{\text{load}}=100\text{mA}$
Short-circuit protection	YES
Reverse Polarity Protection	Yes
Emission	LED Infrared
Interference to external light	according to EN 60947-5-2 : 2020
Impulsive Overvoltage Protection	Yes
Insulation resistance	$>20\text{ M}\Omega$ 500 Vdc, between electronics and housing
Contact resistance	500 Vac 1 min., between electronics and housing

#### Mechanical data

Dimensions	$\text{Ø}18 \times 77$
------------	------------------------

Housing Material	Plastic - PBT / PMMA
Connections	M12 plug
Active Head Material	PMMA
Storage temperature	- 25°C...+70°C
Material	
Diameter/Dimension	M18

#### Test/Approvals

Approvals	CE cULus
Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)

#### Accessories

Supplied Accessories	nuts M18 x 1
----------------------	--------------

#### Generical Data

Dimensions	M18 x 1 /L=77
Operating Temperature	- 25°C...+ 55°C (Without freeze)
Mechanical Protection	IP67

## Datasensing S.r.l.

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973

**date of  
printing**  
24/04/2026  
22:38:08

E-mail  
[info@datasensing.com](mailto:info@datasensing.com)