



S5

G521000

S5-5-G12-00
TUBULAR SENSORS

OVERVIEW

- Wide versatility of optic functions and connections
- High operating distances for all functions
- Models with trimmer adjustment and stability LED
- Rugged and impermeable plastic housing

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	12m
--------------------------	-----

Sensitivity adjustment	n/a
------------------------	-----

Application

Function Principle	Diffuse reflection (medium distance, $\leq 600\text{mm}$)
--------------------	--

Description	Tubular M18 - axial optic
-------------	---------------------------

Functions	Through beam emitter
-----------	----------------------

Outputs

Output type	n/a
-------------	-----

Response time	n/a
---------------	-----

Electrical data

Operating Voltage	10...30VDC
-------------------	------------

LED indicators	Green (powerON)
----------------	-----------------

Time delay before availability	≤200ms
--------------------------------	--------

Emission	LED Infrared
----------	--------------

Mechanical data

Dimensions	Ø18x67
------------	--------

Connections	2m cable
-------------	----------

Material	Plastic ABS / PMMA
----------	--------------------

Test/Approvals

EMC compatibility	EN 60947-5-2
-------------------	--------------

Generical Data

Dimensions	Ø18x67
------------	--------

Operating Temperature	- 15°C...+ 55°C (Without freeze)
-----------------------	----------------------------------

Datasensing
S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

date of
printing
01/04/2026
11:52:21