



S5

H5210230

S5-5-A4-30
TUBULAR SENSORS

OVERVIEW

- Wide versatility of optic functions and connections
- High operating distances for all functions
- Models with trimmer adjustment and stability LED
- Rugged and impermeable plastic housing

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	4m
Sensitivity adjustment	n/a

Application

Function Principle	Diffuse reflection (medium distance, $\leq 600\text{mm}$)
Description	Tubular M18 - axial optic

Functions	Retroreflective
-----------	-----------------

Outputs

Output type	NPN/PNP - Dark/Light sel.
-------------	---------------------------

Response time	1
---------------	---

Electrical data

Operating Voltage	10...30VDC
-------------------	------------

LED indicators	Green (powerON)
----------------	-----------------

Time delay before availability	≤200ms
--------------------------------	--------

Emission	LED Infrared
----------	--------------

Mechanical data

Dimensions	Ø18x67
------------	--------

Material	Plastic ABS / PMMA
----------	--------------------

Connections	2m cable
-------------	----------

Test/Approvals

EMC compatibility	EN 60947-5-2
-------------------	--------------

Generical Data

Dimensions	Ø18x67
------------	--------

Operating Temperature	- 15°C...+ 55°C (Without freeze)
-----------------------	----------------------------------

Datasensing
S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

date of
printing
16/06/2026
07:05:25