



# S5

## H5210430

S5-5-D15-30  
TUBULAR SENSORS

## OVERVIEW

- Wide versatility of optic functions and connections
- High operating distances for all functions
- Models with trimmer adjustment and stability LED
- Rugged and impermeable plastic housing

## TECHNICAL FEATURES

### Detection properties

Nominal sensing distance	15mm
--------------------------	------

Sensitivity adjustment	n/a
------------------------	-----

### Application

Function Principle	Diffuse reflection (medium distance, $\leq 600\text{mm}$ )
--------------------	--

Description	Tubular M18 - axial optic
-------------	---------------------------

Functions	Fix focus beam
-----------	----------------

#### Outputs

Output type	NPN/PNP - Dark/Light sel.
-------------	---------------------------

Response time	1
---------------	---

#### Electrical data

Operating Voltage	10...30VDC
-------------------	------------

LED indicators	Green (powerON)
----------------	-----------------

Time delay before availability	≤200ms
--------------------------------	--------

Emission	LED Infrared
----------	--------------

#### Mechanical data

Dimensions	Ø18x67
------------	--------

Material	Plastic ABS / PMMA
----------	--------------------

Connections	2m cable
-------------	----------

#### Test/Approvals

EMC compatibility	EN 60947-5-2
-------------------	--------------

#### Generical Data

Dimensions	Ø18x67
------------	--------

Operating Temperature	- 15°C...+ 55°C (Without freeze)
-----------------------	----------------------------------

**Datasensing**  
**S.r.l.**

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail  
info@datasensing.com

**date of**  
**printing**  
16/06/2026  
21:26:54