



S65-V

956251030

S65-PA-5-V09-NNN

ADVANCED COLOR AND CONTRAST SENSORS IN COMPACT CASE

OVERVIEW

Color S65-V:

- 3 independent NPN or PNP outputs and RS 485 serial interface
- 3 channel color sensor with 10 tolerance levels
- Wide spectrum white light LED emission and RGB photo-receiver
- 2 push button setting with 4 digit display indicator

Contrast S65-W:

- High 12 bit resolution and 30 kHz switching frequency
- PNP or NPN output and RS 485 serial interface

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	45mm
Spot dimension	Ø 4 mm
Sensitivity adjustment	Teach-in

Application

Function Principle	Color detection
--------------------	-----------------

Description	Compact square case
Optic position	Radial 90°
Functions	Color detection

Outputs

Output type	NPN L/D Selectable
Output Function	L/D Selectable
Switching frequency	1,5 kHz
Response time	0,33

Electrical data

Operating Voltage	10...30VDC
No-Load supply current	≤ 60mA
Load current	≤100mA
Output voltage drop	≤ 2VDC
LED indicators	Yellow (output state) green 4-digit display, 3 OUTPUT STATUS LEDs
Short-circuit protection	YES
Reverse Polarity Protection	Yes
Emission	LED white
Interference to external light	according to EN 60947-5-2 : 2020
Impulsive Overvoltage Protection	Yes

Insulation resistance	>20 MΩ 500 Vdc, between electronics and housing
-----------------------	---

Contact resistance	500 Vac 1 min., between electronics and housing
--------------------	---

Mechanical data

Dimensions	25x50x50
------------	----------

Housing Material	Plastic - ABS / PMMA
------------------	----------------------

Connections	M12 plug
-------------	----------

Active Head Material	PMMA
----------------------	------

Storage temperature	- 20°C...+70°C
---------------------	----------------

Material	
----------	--

Diameter/Dimension	Cubic
--------------------	-------

Test/Approvals

Approvals	CE cULus
-----------	----------

Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)
-----------------------	--

Generical Data

Dimensions	25x50x50
------------	----------

Operating Temperature	- 10°C...+ 55°C
-----------------------	-----------------

Mechanical Protection	IP67
-----------------------	------

**Datasensing
S.r.l.**

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
12/05/2026
17:35:10