



S3N

95B010880

S3N-PH-5-B03-OZ RRX P LASER IOL M8
MINIATURE PHOTOELECTRIC SENSOR

OVERVIEW

- All models with visible and bright red emission
- LED and Laser emission models
- Multiple Background suppression functions
- Shiny and clear object detection
- Single, Double trimmer & Push Button models
- Diffuse proximity up to 100 cm
- Background suppression up to 800 mm (LED trimmer version)
- Polarized RRX 7 m (Red LED emission)
- Polarized RRX 12 m (Red Laser emission)
- Through-beam 20 m and Laser 30 m
- Connection with 2 m Cable or M8 connector
- Rugged IP67 Plastic miniature case
- M3 threaded holes on the front side with metal inserts
- State of the art IO-Link connectivity with extended Smart Tasks



TECHNICAL FEATURES

Detection properties

Nominal sensing distance	10m
Sensitivity adjustment	Push Button TEACH-IN

Minimum sensing distance (blind zone)	0,1m
---------------------------------------	------

Application

Function Principle	Polarized retroreflective
Notes	On R7 reflector (class 1 LASER)
Optic position	Radial 90°
Functions	Polarized retroreflective

Outputs

Output type	IO-Link
Switching frequency	2kHz

Electrical data

Operating Voltage	10...30VDC
No-Load supply current	≤ 35mA
Load current	≤100mA
Leakage current	≤ 400 µA
Output voltage drop	≤2V@Iload=100mA
Max ripple content	≤10%
LED indicators	yellow OUTPUT LED all models, green Power ON LED and user interface interaction during teach, blu LED IO-Link Activity
Short-circuit protection	Yes

Reverse Polarity Protection	Yes
Emission	LASER Red (650nm) class1
Interference to external light	according to EN 60947-5-2 : 2020
Impulsive Overvoltage Protection	Yes
Insulation resistance	>20 MΩ 500 Vdc, between electronics and housing
Contact resistance	500 Vac 1 min., between electronics and housing
0,1μF @Vmax - 1μF @Vmin	Yes

Mechanical data

Housing Material	Plastic Polymer Fiber Glass reinforced
Connections	M8 plug 4pin
Active Head Material	PMMA
Storage temperature	- 25°C...+70°C
Plug connector material	Metal
shaft material	POM, PMMA
Diameter/Dimension	Cubic

Test/Approvals

Approvals	CE cULus CDRH 1 IO-Link
EMC compatibility	EN 60947-5-2


Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)
-----------------------	--

Generical Data

Dimensions	11x31x19 mm
Operating Temperature	-25°C ... 55°C
Mechanical Protection	IP67


CONNECTIONS

Eletrical diagram



OTHERS

Response curves



**Datasensing
S.r.l.**

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
02/08/2025
13:59:34