



# S100

## 950811010

S100-PR-2-A00-PK

THE UNIVERSAL MINIATURE PHOTOELECTRIC SENSORS

## OVERVIEW

- Two threaded front mounting holes
- Two slotted rear mounting holes
- Anti-tampering sensor (no adjustment)
- High speed high resolution RGB contrast sensor available
- Transparent object detection
- M8 connector and cable models
- PNP or NPN models with Light/Dark selection by wire
- Plastic housing, IP67 mechanical protection
- IO-Link COM2 communication protocol
- IO-Link V1.1.2 version
- IO-Link extended parametrization for monitoring and maintenance

## TECHNICAL FEATURES

### Detection properties

Nominal sensing distance	7m
--------------------------	----

Sensitivity adjustment	n/a
------------------------	-----

### Application

Function Principle	Retroreflective
--------------------	-----------------

Description	Miniature universal multi-holes
Optic position	Radial 90°
Functions	Retroreflective

#### Outputs

Output type	PNP L/D selectable
Output Function	L/D selectable
Switching frequency	500Hz
Response time	1ms

#### Electrical data

Operating Voltage	10...30VDC
No-Load supply current	≤ 30mA
Load current	≤100mA
Output voltage drop	≤2V@Iload=100mA
LED indicators	Yellow (status output)
Short-circuit protection	YES
Reverse Polarity Protection	Yes
Emission	LED Infrared
Interference to external light	according to EN 60947-5-2 : 2020
Impulsive Overvoltage Protection	Yes

Insulation resistance	>20 MΩ 500 Vdc, between electronics and housing
-----------------------	---

Contact resistance	500 Vac 1 min., between electronics and housing
--------------------	---

#### Mechanical data

Dimensions	12x32x20
------------	----------

#### Material

Housing material	ABS
------------------	-----

Connections	2m cable
-------------	----------

Active Head Material	PMMA
----------------------	------

Storage temperature	- 25°C...+70°C
---------------------	----------------

Diameter/Dimension	Cubic
--------------------	-------

#### Test/Approvals

Approvals	CE cULus
-----------	----------

Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)
-----------------------	--

#### Generical Data

Dimensions	12x32x20
------------	----------

Operating Temperature	- 25°C...+ 55°C (Without freeze)
-----------------------	----------------------------------

Mechanical Protection	IP67
-----------------------	------

**Datasensing  
S.r.l.**

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail  
[info@datasensing.com](mailto:info@datasensing.com)

**date of  
printing**  
29/05/2026  
19:54:22