



S300

951451090

S300-PR-5-C01-OC

HEAVY DUTY SENSOR FOR OUTDOOR APPLICATIONS AND HARSH ENVIRONMENTS

OVERVIEW

- Industrial plastic housing with IP67 mechanical protection
- Defogging system function
- Double independent timing functions with double time scale from 0-2s or 0-10s, One-Delay, Off Delay, ONE SHOT

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	5m
Sensitivity adjustment	Trimmer

Application

Function Principle	Diffuse beam
Description	Large case vertical mount
Optic position	Radial 90°
Functions	Diffuse beam

Outputs

Output type	NPN/PNP - Dark/Light sel.
-------------	---------------------------

Switching frequency	500Hz
---------------------	-------

Response time	1
---------------	---

Electrical data

Operating Voltage	12...30VDC
-------------------	------------

No-Load supply current	$\leq 30\text{mA}$
------------------------	--------------------

Load current	$\leq 100\text{mA}$
--------------	---------------------

Output voltage drop	$\leq 2,4\text{V}$
---------------------	--------------------

LED indicators	Yellow (output state) Green (stability)
----------------	---

Short-circuit protection	YES
--------------------------	-----

Reverse Polarity Protection	Yes
-----------------------------	-----

Emission	LED Infrared
----------	--------------

Interference to external light	according to EN 60947-5-2 : 2020
--------------------------------	----------------------------------

Impulsive Overvoltage Protection	Yes
----------------------------------	-----

Insulation resistance	$>20\text{ M}\Omega$ 500 Vdc, between electronics and housing
-----------------------	---

Contact resistance	500 Vac 1 min., between electronics and housing
--------------------	---

Mechanical data

Dimensions	25x85x70
Housing Material	PBT Fiber Glass reinforced
Connections	M12 plug
Active Head Material	PMMA
Storage temperature	- 40°C...+70°C
Material	Plastic - PBT / PC
Diameter/Dimension	Cubic

Test/Approvals

Approvals	CE cULus
Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)

Generical Data

Dimensions	25x85x70
Operating Temperature	- 40°C...+ 55°C
Mechanical Protection	IP67

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
02/04/2026
12:30:47