



# S300

## 951451170

### S300-PR-5-M06-OC

HEAVY DUTY SENSOR FOR OUTDOOR APPLICATIONS AND HARSH ENVIRONMENTS

## OVERVIEW

- Industrial plastic housing with IP67 mechanical protection
- Defogging system function
- Double independent timing functions with double time scale from 0-2s or 0-10s, One-Delay, Off Delay, ONE SHOT

## TECHNICAL FEATURES

### Detection properties

|                          |      |
|--------------------------|------|
| Nominal sensing distance | 2,5m |
|--------------------------|------|

|                        |         |
|------------------------|---------|
| Sensitivity adjustment | Trimmer |
|------------------------|---------|

### Application

|                    |                        |
|--------------------|------------------------|
| Function Principle | Background suppression |
|--------------------|------------------------|

|             |                           |
|-------------|---------------------------|
| Description | Large case vertical mount |
|-------------|---------------------------|

|                |            |
|----------------|------------|
| Optic position | Radial 90° |
|----------------|------------|

|           |                        |
|-----------|------------------------|
| Functions | Background suppression |
|-----------|------------------------|

|                                  |                                                 |
|----------------------------------|-------------------------------------------------|
| Outputs                          |                                                 |
| Output type                      | NPN/PNP - Dark/Light sel.                       |
| Switching frequency              | 250Hz                                           |
| Response time                    | 2                                               |
| Electrical data                  |                                                 |
| Operating Voltage                | 12...30VDC                                      |
| No-Load supply current           | ≤ 35mA                                          |
| Load current                     | ≤100mA                                          |
| Output voltage drop              | ≤ 2,4V                                          |
| LED indicators                   | Yellow (output state) Green (stability)         |
| Short-circuit protection         | YES                                             |
| Reverse Polarity Protection      | Yes                                             |
| Emission                         | LED Infrared                                    |
| Interference to external light   | according to EN 60947-5-2 : 2020                |
| Impulsive Overvoltage Protection | Yes                                             |
| Insulation resistance            | >20 MΩ 500 Vdc, between electronics and housing |
| Contact resistance               | 500 Vac 1 min., between electronics and housing |
| Mechanical data                  |                                                 |

|                      |                            |
|----------------------|----------------------------|
| Dimensions           | 25x85x70                   |
| Material             | Plastic - PBT / PC         |
| Housing material     | PBT Fiber Glass reinforced |
| Connections          | M12 plug                   |
| Active Head Material | PMMA                       |
| Storage temperature  | - 40°C...+70°C             |
| Diameter/Dimension   | Cubic                      |

#### Test/Approvals

|                       |                                                                        |
|-----------------------|------------------------------------------------------------------------|
| Approvals             | CE cULus                                                               |
| Shocks and vibrations | 0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6) |

#### Generical Data

|                       |                 |
|-----------------------|-----------------|
| Dimensions            | 25x85x70        |
| Operating Temperature | - 40°C...+ 55°C |
| Mechanical Protection | IP67            |

#### **Datasensing S.r.l.**

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail  
info@datasensing.com

**date of  
printing**  
10/08/2026  
01:48:13