



# S300

## 951451250

### S300-PR-1-F01-RX

HEAVY DUTY SENSOR FOR OUTDOOR APPLICATIONS AND HARSH ENVIRONMENTS

## OVERVIEW

- Industrial plastic housing with IP67 mechanical protection
- Defogging system function
- Double independent timing functions with double time scale from 0-2s or 0-10s, One-Delay, Off Delay, ONE SHOT

## TECHNICAL FEATURES

### Detection properties

|                          |         |
|--------------------------|---------|
| Nominal sensing distance | 60m     |
| Sensitivity adjustment   | Trimmer |

### Application

|                    |                           |
|--------------------|---------------------------|
| Function Principle | Through beam receiver     |
| Description        | Large case vertical mount |
| Optic position     | Radial 90°                |
| Functions          | Through beam receiver     |

|                                  |                                                 |
|----------------------------------|-------------------------------------------------|
| Outputs                          |                                                 |
| Output type                      | Relay SPDT                                      |
| Switching frequency              | 25Hz                                            |
| Response time                    | 20                                              |
| Electrical data                  |                                                 |
| Operating Voltage                | 24...240 VAC                                    |
| No-Load supply current           | ≤ 3VA                                           |
| Load current                     | ≤ 3A                                            |
| Output voltage drop              | ≤ 2,4V                                          |
| LED indicators                   | Yellow (output state) Green (stability)         |
| Short-circuit protection         | YES                                             |
| Reverse Polarity Protection      | Yes                                             |
| Emission                         | n/a                                             |
| Interference to external light   | according to EN 60947-5-2 : 2020                |
| Impulsive Overvoltage Protection | Yes                                             |
| Insulation resistance            | >20 MΩ 500 Vdc, between electronics and housing |
| Contact resistance               | 500 Vac 1 min., between electronics and housing |
| Mechanical data                  |                                                 |

|                      |                            |
|----------------------|----------------------------|
| Dimensions           | 25x85x70                   |
| Material             | Plastic - PBT / PC         |
| Housing material     | PBT Fiber Glass reinforced |
| Connections          | Terminal block             |
| Active Head Material | PMMA                       |
| Storage temperature  | - 40°C...+70°C             |
| Diameter/Dimension   | Cubic                      |

#### Test/Approvals

|                       |                                                                        |
|-----------------------|------------------------------------------------------------------------|
| Approvals             | CE cULus                                                               |
| Shocks and vibrations | 0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6) |

#### Generical Data

|                       |                 |
|-----------------------|-----------------|
| Dimensions            | 25x85x70        |
| Operating Temperature | - 40°C...+ 55°C |
| Mechanical Protection | IP67            |

#### Datasensing S.r.l.

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail  
info@datasensing.com

**date of  
printing**  
10/08/2026  
00:52:11