



S45

950411270

S45-PR-2-M03-NH

HIGH PERFORMANCE EUROPEAN STYLE MINIATURE
SENSOR ALL-IN-ONE FAMILY

OVERVIEW

- Red LED and Laser emissions
- Precise risk free laser class 1 emission
- Diffused LED proximity 800mm
- Background Suppression 400mm
- Retroreflective Class 1 Laser 15m/Red LED 7m
- Through beam Class 1 Laser 20m/Red LED 15m
- IP69K housing
- 2m Cable or metal M8 4 pole version
- PNP or NPN output with remote teach in input
- High speed RGB and white emission contrast sensor
- High precision distance sensor up to 200 mm

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	200mm
--------------------------	-------

Sensitivity adjustment	Teach-in
------------------------	----------

Application

Function Principle	Background suppression
--------------------	------------------------

Description	Miniature european style rear holes
Optic position	Radial 90°
Functions	Background suppression

Outputs	
Output type	NPN L/D Selectable
Output Function	L/D Selectable
Response time	0,5

Electrical data	
Operating Voltage	10...30VDC
No-Load supply current	≤ 30mA
Load current	≤100mA
Output voltage drop	≤2V@Iload=100mA
LED indicators	Green (PowerON) Yellow (status output)
Short-circuit protection	YES
Reverse Polarity Protection	Yes
Emission	LED Red (632 nm)
Interference to external light	according to EN 60947-5-2 : 2020
Impulsive Overvoltage Protection	Yes
Insulation resistance	>20 MΩ 500 Vdc, between electronics and housing

Contact resistance	500 Vac 1 min., between electronics and housing
--------------------	---

Mechanical data

Dimensions	12x34x20
Material	Plastic ABS / PMMA
Housing material	ABS(Housing), PMMA (Optics)
Connections	2m cable
Active Head Material	PMMA
Storage temperature	- 25°C...+70°C
Diameter/Dimension	cubic

Test/Approvals

Approvals	CE cULus
Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)

Generical Data

Dimensions	12x34x20
Operating Temperature	- 25°C...+ 55°C (Without freeze)
Mechanical Protection	IP67 & IP69K

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

11/08/2026
02:17:33