



# S6

## 950201150

S6-5-C200

MULTIVOLTAGE 50X50 MM COMPACT SENSORS SERIES

## OVERVIEW

- 50x50 mm compact dimensions
- Free voltage Vac/Vdc models with relay output
- 10-30 Vdc model with transistor output
- Standard cable or M12 4-pole connection

## TECHNICAL FEATURES

### Detection properties

Nominal sensing distance	2m
--------------------------	----

Sensitivity adjustment	Trimmer
------------------------	---------

### Application

Function Principle	Diffuse beam
--------------------	--------------

Description	Compact square case
-------------	---------------------

Functions	Diffuse beam
-----------	--------------

### Outputs

Output type	NPN / PNP L/D Selectable
Output Function	L/D Selectable
Switching frequency	500Hz
Response time	1ms

#### Electrical data

Operating Voltage	10...30VDC
No-Load supply current	≤ 30mA
Load current	≤100mA
Output voltage drop	≤1,5V@Iload=100mA
LED indicators	Red OUTPUT
Short-circuit protection	YES
Reverse Polarity Protection	Yes
Emission	LED Infrared
Interference to external light	according to EN 60947-5-2 : 2020
Impulsive Overvoltage Protection	Yes
Insulation resistance	>20 MΩ 500 Vdc, between electronics and housing
Contact resistance	500 Vac 1 min., between electronics and housing

#### Mechanical data

Dimensions	18x50x50
Housing Material	ABS
Connections	M12 plug
Active Head Material	PMMA
Storage temperature	- 25°C...+70°C
Material	
Diameter/Dimension	Cubic

#### Test/Approvals

Approvals	CE cULus
Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)

#### Generical Data

Dimensions	18x50x50
Operating Temperature	- 25°C...+ 55°C (Without freeze)
Mechanical Protection	IP65

## Datasensing S.r.l.

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail  
info@datasensing.com

**date of  
printing**  
03/04/2026  
05:40:42