



S6

S937330090

S6-1-A6

MULTIVOLTAGE 50X50 MM COMPACT SENSORS SERIES

OVERVIEW

- 50x50 mm compact dimensions
- Free voltage Vac/Vdc models with relay output
- 10-30 Vdc model with transistor output
- Standard cable or M12 4-pole connection

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	6m
--------------------------	----

Sensitivity adjustment	n/a
------------------------	-----

Application

Function Principle	Retroreflective
--------------------	-----------------

Description	Compact square case
-------------	---------------------

Functions	Retroreflective
-----------	-----------------

Outputs

Output type	Relay SPDT L/D selectable by trimmer
Output Function	L/D selectable by trimmer
Switching frequency	16Hz
Response time	30ms

Electrical data

Operating Voltage	24...240 VAC
No-Load supply current	≤ 40mA
Load current	≤3A
LED indicators	Red OUTPUT
Emission	LED Infrared

Mechanical data

Dimensions	18x50x50
Material	
Housing material	ABS
Connections	2m cable
Active Head Material	PMMA
Storage temperature	- 25°C...+70°C
Diameter/Dimension	Cubic

Test/Approvals

EMC compatibility	EN 60947-5-2
-------------------	--------------

Generical Data

Dimensions	18x50x50
------------	----------

Operating Temperature	- 25°C...+ 55°C (Without freeze)
-----------------------	----------------------------------

Mechanical Protection	IP65
-----------------------	------

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
10/08/2026
00:30:03