



S60

956201010

S60-PA-5-U08-NH

EXTENDED RANGE OF STANDARD "ONE FOR ALL"
PHOTOELECTRIC COMPACT SENSORS

OVERVIEW

- Complete range of optic functions, basic, advanced and laser class 1
- Models with coaxial optics for polarized retroreflective, contrast and luminescence sensors
- Trimmer or EASY touch™ setting with
- Remote, Keylock and Delay functions
- Standard cable or M12 connection with standard NPN or PNP configuration

TECHNICAL FEATURES

Detection properties

| | |
|--------------------------|------|
| Nominal sensing distance | 40mm |
|--------------------------|------|

| | |
|------------------------|----------|
| Sensitivity adjustment | Teach-in |
|------------------------|----------|

Application

| | |
|--------------------|----------------------------|
| Function Principle | Luminescent mark detection |
|--------------------|----------------------------|

| | |
|-------------|---------------------|
| Description | Compact square case |
|-------------|---------------------|

| | |
|----------------|-------|
| Optic position | axial |
|----------------|-------|

| | |
|-----------|----------------------------|
| Functions | Luminescent mark detection |
|-----------|----------------------------|

Outputs

| | |
|-------------|--------------------|
| Output type | NPN L/D Selectable |
|-------------|--------------------|

| | |
|-----------------|----------------|
| Output Function | L/D Selectable |
|-----------------|----------------|

| | |
|---------------|-------------|
| Response time | 250 μ s |
|---------------|-------------|

Electrical data

| | |
|-------------------|------------|
| Operating Voltage | 10...30VDC |
|-------------------|------------|

| | |
|------------------------|-------------|
| No-Load supply current | \leq 40mA |
|------------------------|-------------|

| | |
|--------------|--------------|
| Load current | \leq 100mA |
|--------------|--------------|

| | |
|---------------------|-----------------------|
| Output voltage drop | \leq 2V@Iload=100mA |
|---------------------|-----------------------|

| | |
|--------------------|--------------|
| Max ripple content | \leq 2 Vpp |
|--------------------|--------------|

| | |
|----------------|--|
| LED indicators | Yellow (status output) Green/red READY/ERROR LED |
|----------------|--|

| | |
|--------------------------|-----|
| Short-circuit protection | YES |
|--------------------------|-----|

| | |
|-----------------------------|-----|
| Reverse Polarity Protection | Yes |
|-----------------------------|-----|

| | |
|----------|--------|
| Emission | LED UV |
|----------|--------|

| | |
|--------------------------------|----------------------------------|
| Interference to external light | according to EN 60947-5-2 : 2020 |
|--------------------------------|----------------------------------|

| | |
|----------------------------------|-----|
| Impulsive Overvoltage Protection | Yes |
|----------------------------------|-----|

| | |
|-----------------------|---|
| Insulation resistance | >20 M Ω 500 Vdc, between electronics and housing |
|-----------------------|---|

| | |
|--------------------|---|
| Contact resistance | 500 Vac 1 min., between electronics and housing |
|--------------------|---|

Mechanical data

| | |
|------------|----------|
| Dimensions | 15X50X50 |
|------------|----------|

| | |
|------------------|----------|
| Housing Material | ABS/PMMA |
|------------------|----------|

| | |
|-------------|----------|
| Connections | M12 plug |
|-------------|----------|

| | |
|----------------------|------|
| Active Head Material | PMMA |
|----------------------|------|

| | |
|---------------------|----------------|
| Storage temperature | - 25°C...+70°C |
|---------------------|----------------|

| | |
|----------|--|
| Material | |
|----------|--|

| | |
|--------------------|-------|
| Diameter/Dimension | Cubic |
|--------------------|-------|

Test/Approvals

| | |
|-----------|----------|
| Approvals | CE cULus |
|-----------|----------|

| | |
|-----------------------|--|
| Shocks and vibrations | 0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6) |
|-----------------------|--|

Generical Data

| | |
|------------|----------|
| Dimensions | 15X50X50 |
|------------|----------|

| | |
|-----------------------|----------------------------------|
| Operating Temperature | - 25°C...+ 55°C (Without freeze) |
|-----------------------|----------------------------------|

| | |
|-----------------------|------|
| Mechanical Protection | IP67 |
|-----------------------|------|

Datasensing
S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)

date of
printing
05/04/2026
11:31:34

Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com