



# S60

## 956201070

### S60-PA-5-G00-XG

EXTENDED RANGE OF STANDARD "ONE FOR ALL"  
PHOTOELECTRIC COMPACT SENSORS

## OVERVIEW

- Complete range of optic functions, basic, advanced and laser class 1
- Models with coaxial optics for polarized retroreflective, contrast and luminescence sensors
- Trimmer or EASY touch<sup>TM</sup> setting with
- Remote, Keylock and Delay functions
- Standard cable or M12 connection with standard NPN or PNP configuration

## TECHNICAL FEATURES

### Detection properties

Nominal sensing distance	20m
Sensitivity adjustment	Trimmer

### Application

Function Principle	Through beam emitter
Description	Compact square case
Optic position	axial

Functions	Through beam emitter
Outputs	
Output type	n/a
Response time	n/a
Electrical data	
Operating Voltage	10...30VDC
No-Load supply current	≤ 40mA
Load current	≤100mA
Output voltage drop	≤2V@Iload=100mA
Max ripple content	≤2 Vpp
LED indicators	Yellow (status output)
Short-circuit protection	YES
Reverse Polarity Protection	Yes
Emission	LED Infrared
Interference to external light	according to EN 60947-5-2 : 2020
Impulsive Overvoltage Protection	Yes
Insulation resistance	>20 MΩ 500 Vdc, between electronics and housing
Contact resistance	500 Vac 1 min., between electronics and housing

#### Mechanical data

Dimensions	15X50X50
------------	----------

Housing Material	ABS/PMMA
------------------	----------

Connections	M12 plug
-------------	----------

Active Head Material	PMMA
----------------------	------

Storage temperature	- 25°C...+70°C
---------------------	----------------

Material	
----------	--

Diameter/Dimension	Cubic
--------------------	-------

#### Test/Approvals

Approvals	CE cULus
-----------	----------

Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)
-----------------------	--

#### Generical Data

Dimensions	15X50X50
------------	----------

Operating Temperature	- 25°C...+ 55°C (Without freeze)
-----------------------	----------------------------------

Mechanical Protection	IP67
-----------------------	------

#### **Datasensing S.r.l.**

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail

**date of  
printing**  
21/07/2025  
18:28:40

info@datasensing.com