



S60

956201400

S60-PA-2-W08-PH

EXTENDED RANGE OF STANDARD "ONE FOR ALL"
PHOTOELECTRIC COMPACT SENSORS

OVERVIEW

- Complete range of optic functions, basic, advanced and laser class 1
- Models with coaxial optics for polarized retroreflective, contrast and luminescence sensors
- Trimmer or EASY touch™ setting with
- Remote, Keylock and Delay functions
- Standard cable or M12 connection with standard NPN or PNP configuration

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	20mm
--------------------------	------

Sensitivity adjustment	Teach-in
------------------------	----------

Application

Function Principle	Contrast mark detection
--------------------	-------------------------

Description	Compact square case
-------------	---------------------

Optic position	axial
----------------	-------

Functions	Contrast mark detection
Outputs	
Output type	PNP L/D selectable
Output Function	L/D selectable
Switching frequency	5Khz
Response time	100µs (5kHz)
Electrical data	
Operating Voltage	10...30VDC
No-Load supply current	≤ 40mA
Load current	≤100mA
Output voltage drop	≤2V@Iload=100mA
Max ripple content	≤2 Vpp
LED indicators	Yellow (status output) Green/red READY/ERROR LED
Short-circuit protection	YES
Reverse Polarity Protection	Yes
Emission	LED white
Interference to external light	according to EN 60947-5-2 : 2020
Impulsive Overvoltage Protection	Yes

Insulation resistance	>20 MΩ 500 Vdc, between electronics and housing
Contact resistance	500 Vac 1 min., between electronics and housing

Mechanical data

Dimensions	15X50X50
Material	
Housing material	ABS/PMMA
Connections	2m cable
Active Head Material	PMMA
Storage temperature	- 25°C...+70°C
Diameter/Dimension	Cubic

Test/Approvals

Approvals	CE cULus
Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)

Generical Data

Dimensions	15X50X50
Operating Temperature	- 25°C...+ 55°C (Without freeze)
Mechanical Protection	IP67

**Datasensing
S.r.l.**

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
10/08/2026
00:47:22