



S8

950801260

S8-PR-5-C01-NN

COMPACT SIZE AND HIGH PERFORMANCE FOR THE MOST CHALLENGING DETECTION APPLICATIONS LINKED TO YOUR INDUSTRY 4.0 APPLICATIONS

# OVERVIEW

- Compact dimensions (14x42x25 mm)
- Background suppression for transparent and shiny objects
- Contrast sensors up to 25 kHz switching frequency
- Extremely focused spot, under 1 mm (LASER model)
- Very high resolution LASER models
- INOX AISI 316L model
- Extended IO-Link parametrization with counter
- All output fully PNP/NPN/PP IO-Link configurable
- IO-link COM2
- IO-Link dual channel with no jitter addition

# TECHNICAL FEATURES

## Detection properties

Nominal sensing distance 500mm

Sensitivity adjustment Trimmer

## Application

Function Principle Diffuse beam

Description Compact slim case

|                                  |                                                          |
|----------------------------------|----------------------------------------------------------|
| Optic position                   | Radial 90°                                               |
| Functions                        | Diffuse beam                                             |
| Outputs                          |                                                          |
| Output type                      | NPN L/D Selectable                                       |
| Output Function                  | L/D Selectable                                           |
| Response time                    | 0,5                                                      |
| Electrical data                  |                                                          |
| Operating Voltage                | 12...30VDC                                               |
| No-Load supply current           | ≤ 30mA                                                   |
| Output voltage drop              | ≤2V@Iload=100mA                                          |
| LED indicators                   | Yellow (status output) or (output/alarm) Green (powerON) |
| Short-circuit protection         | YES                                                      |
| Reverse Polarity Protection      | Yes                                                      |
| Emission                         | LED Red                                                  |
| Interference to external light   | according to EN 60947-5-2 : 2020                         |
| Impulsive Overvoltage Protection | Yes                                                      |
| Insulation resistance            | >20 MΩ 500 Vdc, between electronics and housing          |
| Contact resistance               | 500 Vac 1 min., between electronics and housing          |

## Mechanical data

|                      |                             |
|----------------------|-----------------------------|
| Dimensions           | 14x43x25                    |
| Material             | Plastic - ABS / PMMA        |
| Housing material     | ABS(Housing), PMMA (Optics) |
| Connections          | M8 plug 4pin                |
| Active Head Material | PMMA                        |
| Storage temperature  | - 25°C...+70°C              |
| Diameter/Dimension   | Cubic                       |

## Test/Approvals

|                       |                                                                        |
|-----------------------|------------------------------------------------------------------------|
| Approvals             | CE cULus                                                               |
| Shocks and vibrations | 0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6) |

## Generical Data

|                       |                                  |
|-----------------------|----------------------------------|
| Dimensions            | 14x43x25                         |
| Operating Temperature | - 25°C...+ 55°C (Without freeze) |
| Mechanical Protection | IP67                             |

## Datasensing S.r.l.

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail

**date of  
printing**  
10/08/2026  
00:06:30

info@datasensing.com