



S8

950801530

S8-PR-3-F01-NN
COMPACT SIZE AND HIGH PERFORMANCE FOR THE MOST CHALLENGING DETECTION APPLICATIONS LINKED TO YOUR INDUSTRY 4.0 APPLICATIONS

OVERVIEW

- Compact dimensions (14x42x25 mm)
- Background suppression for transparent and shiny objects
- Contrast sensors up to 25 kHz switching frequency
- Extremely focused spot, under 1 mm (LASER model)
- Very high resolution LASER models
- INOX AISI 316L model
- Extended IO-Link parametrization with counter
- All output fully PNP/NPN/PP IO-Link configurable
- IO-link COM2
- IO-Link dual channel with no jitter addition

TECHNICAL FEATURES

Detection properties	
Nominal sensing distance	30m
Sensitivity adjustment	Trimmer
Application	
Function Principle	Through beam receiver
Description	Compact slim case

Optic position	Radial 90°
Functions	Through beam receiver
Outputs	
Output type	NPN L/D Selectable
Output Function	L/D Selectable
Response time	0,5
Electrical data	
Operating Voltage	12...30VDC
No-Load supply current	≤ 20mA
Output voltage drop	≤2V@Iload=100mA
LED indicators	Yellow (status output) or (output/alarm) Green (powerON)
Short-circuit protection	YES
Reverse Polarity Protection	Yes
Emission	n/a
Interference to external light	according to EN 60947-5-2 : 2020
Impulsive Overvoltage Protection	Yes
Insulation resistance	>20 MΩ 500 Vdc, between electronics and housing
Contact resistance	500 Vac 1 min., between electronics and housing

Mechanical data

Dimensions	14x43x25
Material	Plastic - ABS / PMMA
Housing material	ABS(Housing), PMMA (Optics)
Connections	150mm PVC cable + M12 plug
Active Head Material	PMMA
Storage temperature	- 25°C...+70°C
Diameter/Dimension	Cubic

Test/Approvals

Approvals	CE cULus
Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)

Generical Data

Dimensions	14x43x25
Operating Temperature	- 25°C...+ 55°C (Without freeze)
Mechanical Protection	IP67

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail

**date of
printing**
10/08/2026
01:37:24

info@datasensing.com