



# S3Z

## 95B010070

### S3Z-PR-5-C01-PD

ADVANCED GLOBAL STYLE MINIATURE PHOTOELECTRIC  
SENSOR

## OVERVIEW

- 50-250 mm background suppression
- 0.7 m proximity, 150 mm with narrow beam
- 4 m polarized retroreflective
- 15 m through beam
- Light and dark trimmer models
- Standard 3-wire output configuration

## TECHNICAL FEATURES

### Detection properties

Nominal sensing distance	150mm
--------------------------	-------

Sensitivity adjustment	Trimmer
------------------------	---------

### Application

Function Principle	Diffuse beam
--------------------	--------------

Description	Miniature global standard front holes
-------------	---------------------------------------

Optic position	Radial 90°
----------------	------------

Functions	Diffuse beam
-----------	--------------

#### Outputs

Output type	PNP Don
-------------	---------

Output Function	Don
-----------------	-----

Switching frequency	500Hz
---------------------	-------

Response time	1
---------------	---

#### Electrical data

Operating Voltage	10...30VDC
-------------------	------------

No-Load supply current	$\leq 30\text{mA}$
------------------------	--------------------

Load current	$\leq 100\text{mA}$
--------------	---------------------

Output voltage drop	$\leq 2\text{V}@I_{\text{load}}=100\text{mA}$
---------------------	---

Short-circuit protection	YES
--------------------------	-----

Reverse Polarity Protection	Yes
-----------------------------	-----

Emission	LED Red (665 nm)
----------	------------------

Interference to external light	according to EN 60947-5-2 : 2020
--------------------------------	----------------------------------

Impulsive Overvoltage Protection	Yes
----------------------------------	-----

Insulation resistance	$>20\text{ M}\Omega$ 500 Vdc, between electronics and housing
-----------------------	---

Contact resistance	500 Vac 1 min., between electronics and housing
--------------------	---

## Mechanical data

Dimensions	11x32x20
Housing Material	Plastic PBT / PMMA
Connections	M8 plug 4pin
Active Head Material	PMMA
Storage temperature	- 40°C...+70°C
Material	
Diameter/Dimension	Cubic

## Test/Approvals

Approvals	CE cULus
EMC compatibility	EN 60947-5-2
Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)

## Generical Data

Dimensions	11x32x20
Operating Temperature	- 25°C...+ 55°C
Mechanical Protection	IP67

## **Datasensing S.r.l.**

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411

**date of  
printing**  
19/04/2026  
23:21:24

Fax 059 253973

E-mail

[info@datasensing.com](mailto:info@datasensing.com)