



FY

FY2/0N-0A

**Photo.DIN rail,NPN-NO/NC,Cable,Fiber
amp**

ADVANCED FIBER AMPLIFIERS

OVERVIEW



TECHNICAL FEATURES

Detection properties

Nominal sensing distance	Depending on optical fibres used
Repeat Accuracy	$\leq 5\%$
Sensitivity adjustment	Teach-in

Application

Function Principle	Optic fiber amplifier
Notes	Delay ON/OFF One Shot
Optic position	Axial

Outputs

Output type	NPN L/D Selectable
Output Function	L/D Selectable
Switching frequency	12,5 KHz(HIGH SPEED) 2 KHz (FINE) 500 Hz (SUPER) 31,25 Hz(MEGA)
Response time	40µs(HIGH SPEED) 250 µs (FINE) 1ms (SUPER) 16ms(MEGA)

Electrical data

Operating Voltage	12...24VDC
No-Load supply current	$\leq 50\text{mA}$
Load current	$\leq 100\text{mA}$
Leakage current	$\leq 10\mu\text{A}$
Output voltage drop	$\leq 1,5\text{V}@I_{\text{load}}=100\text{mA}$
Max ripple content	$\leq 10\%$
LED indicators	Red (output state) Red (Signal level -4 digits) Green (Threshold - 4 digits)
Time delay before availability	$\leq 200\text{ms}$
Short-circuit protection	Yes
Reverse Polarity Protection	Yes
Emission	LED Red (680nm)
Interference to external light	20.000lux (incandescent lamp), 30.000lux (sunlight)

Mechanical data

Dimensions	71,8 x 30,3 x 9,8 mm
------------	----------------------

Housing material	PC
------------------	----

Weight	80 g (approx.)
--------	----------------

Connections	2m PVC cable
-------------	--------------

Operating temperature	- 20°C...+ 55°C (without freeze)
-----------------------	----------------------------------

Diameter/Dimension	Cubic
--------------------	-------

Test/Approvals

Approvals	CE
-----------	----

EMC compatibility	EN 60947-5-2
-------------------	--------------

Degree of protection	IP64
----------------------	------

Accessories

Supplied Accessories	DIN mounting bracket
----------------------	----------------------

Generical Data


Dimensions	71,8 x 30,3 x 9,8 mm
------------	----------------------

Operating Temperature	- 20°C...+ 55°C (Without freeze)
-----------------------	----------------------------------

Mechanical Protection	IP64
-----------------------	------

OTHERS

Dimensions



Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
10/08/2026
00:36:09