



FY

FY3/0P-0A

**Photo.DIN rail,PNP-NO/NC,Cable,Fiber
amp**
ADVANCED FIBER AMPLIFIERS

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	Depending on optical fibres used
Repeat Accuracy	≤ 5%
Sensitivity adjustment	Teach-in

Application

Function Principle	Optic fiber amplifier
Notes	Delay ON/OFF One Shot Anti mutual interference
Optic position	Axial

Outputs

Output type	PNP L/D Selectable
Output Function	L/D Selectable

Switching frequency	1Khz
Response time	OFF: 100µs(HIGH SPEED) 250 µs (FINE) 1ms (SUPER) 8ms(MEGA)

Electrical data

Operating Voltage	12...24VDC
No-Load supply current	≤ 40mA
Load current	≤100mA
Leakage current	≤ 10µA
Output voltage drop	≤1V@Iload=100mA
Max ripple content	≤10%
LED indicators	Red (output state) Red (Signal level -4 digits) Green (Threshold - 4 digits)
Time delay before availability	≤200ms
Short-circuit protection	Yes
Reverse Polarity Protection	Yes
Emission	LED Red (680nm)
Interference to external light	20.000lux (incandescent lamp), 30.000lux (sunlight)

Mechanical data

Dimensions	71,8 x 30,3 x 9,8 mm
Housing material	PC
Weight	80 g (approx.)

Connections	2m PVC cable
-------------	--------------

Operating temperature	- 20°C...+ 55°C (without freeze)
-----------------------	----------------------------------

Diameter/Dimension	Cubic
--------------------	-------

Test/Approvals

Approvals	CE
-----------	----

EMC compatibility	EN 60947-5-2
-------------------	--------------

Degree of protection	IP64
----------------------	------

Accessories

Supplied Accessories	DIN mounting bracket
----------------------	----------------------

Generical Data

Dimensions	71,8 x 30,3 x 9,8 mm
------------	----------------------

Operating Temperature	- 20°C...+ 55°C (Without freeze)
-----------------------	----------------------------------

Mechanical Protection	IP64
-----------------------	------

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
10/08/2026
03:21:14