



S7

950551140

S7-8-E-P

FIBER OPTIC AMPLIFIERS IN A DIN RAIL COMPATIBLE
FORMAT FOR SMALL OBJECT DETECTION IN LIMITED
SPACES

OVERVIEW

- High-resolution models with integrated display
- 12 bit resolution and 50 μ s response time
- Trimmer or teach-in models
- Wide range of accessory fiber optics
- 4 wire NO/NC output or Remote teach input

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	100mm
--------------------------	-------

Sensitivity adjustment	Trimmer
------------------------	---------

Application

Function Principle	Optic fiber amplifier
--------------------	-----------------------

Description	Compact case without display
-------------	------------------------------

Optic position	axial
----------------	-------

Functions	Optic fiber amplifier
-----------	-----------------------

Outputs

Output type	PNP L/D selectable
Output Function	L/D selectable
Switching frequency	1Khz (low speed)
Response time	500 μ s (low speed)

Electrical data

Operating Voltage	12...24VDC \pm 10%
No-Load supply current	\leq 30mA
Load current	\leq 100mA
Output voltage drop	\leq 1,2V@Iload=100mA
LED indicators	yellow (output state) green (stability, delay) green/red (Read/error)
Short-circuit protection	YES
Reverse Polarity Protection	Yes
Emission	LED Red (670 nm)
Interference to external light	according to EN 60947-5-2 : 2020
Impulsive Overvoltage Protection	Yes
Insulation resistance	>20 M Ω 500 Vdc, between electronics and housing
Contact resistance	500 Vac 1 min., between electronics and housing

Mechanical data

Dimensions	10x40x65
Housing Material	ABS(Housing), PMMA (Optics)
Connections	M8 plug 4pin
Active Head Material	PMMA
Storage temperature	- 25°C...+70°C
Material	Plastic ABS / PC
Diameter/Dimension	Cubic

Test/Approvals

Approvals	CE cULus
Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)

Generical Data

Dimensions	10x40x65
Operating Temperature	- 25°C...+ 55°C (Without freeze)
Mechanical Protection	IP67 with cover

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973

**date of
printing**
04/04/2026
15:40:07

E-mail
info@datasensing.com