



DATAVS2

959951220

DATAVS2-06-RE-PRO

DATAVS2 VISION SENSORS OFFER EASY CONFIGURABILITY

OVERVIEW

Flexible and intuitive setup via PC through Ethernet

- Memorisation of 20 inspections
- 14 different controls
- 360° Contour Match for Professional models
- Logical operators: AND, OR, NOT, NAND, NOR, ecc.
- TURBO mode to double elaboration speed
- VSM compatibility
- Inspection & Identification functionalities together available on Professional models

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	500mm
--------------------------	-------

Sensitivity adjustment	Teach-in/GUI
------------------------	--------------

Application

Function Principle	ID and 360° pattern matching
--------------------	------------------------------

Description	Block style case - Lens 6 mm
-------------	------------------------------

Optic position	Radial 90°
Functions	ID and 360° pattern matching
Outputs	
Output type	3xPNP, RS232, Ethernet
Response time	50
Electrical data	
Operating Voltage	24VDC
Short-circuit protection	YES
Reverse Polarity Protection	Yes
Emission	LED Red
Impulsive Overvoltage Protection	Yes
Insulation resistance	>20 MΩ 500 Vdc, between electronics and housing
Contact resistance	500 Vac 1 min., between electronics and housing
Mechanical data	
Dimensions	52x60x40
Material	
Housing material	Metal - Aluminium / ABS
Connections	M12 plug

Active Head Material	PMMA
Storage temperature	- 25°C...+70°C

Test/Approvals

Approvals	CE cULus
Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)

Generical Data

Dimensions	52x60x40
------------	----------

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
10/08/2026
02:03:47