



DATAVS2

95A255450

CV-A1-36-B-10

THE RIGHT CONNECTION FOR YOUR PHOTOELECTRIC
SENSORS FOR INDUSTRIAL ENVIRONMENT

OVERVIEW

- M8 and M12, axial or radial female connectors
- Standard length cables: 2, 3, 5, 7, 10, 15, 25 or 50m
- 3, 4, 5, 8 or 12 poles
- Shielded or unshielded models
- P.U.R. coated models for use in harsh environments
- P.V.C. coated models for standard use
- Standard M12 4 pole non-cabled connectors
- The cable jacket maybe marked 300V only as insulation voltage between wires, the operational voltage is 24Vdc or 10-30Vdc, less than 80 V required by CCC-China

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	n/a
Sensitivity adjustment	n/a

Application

Function Principle	DVS2 cable/connector
Description	Straight female shielded

Functions

DVS2 cable/connector

Outputs

Output type n/a

Response time n/a

Electrical data

Operating Voltage n/a

Emission n/a

Mechanical data

Dimensions L=10m

Housing Material PVC (Black)

Connections M12 plug 8pin

Storage temperature - 25°C...+70°C

Material

Generical Data

Dimensions L=10m

**Datasensing
S.r.l.**

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail

**date of
printing**

28/01/2026
03:34:02

info@datasensing.com