



DATAVS2

95A901480

DataVS2-VSM

DATAVS2 VISION SENSORS OFFER EASY CONFIGURABILITY

OVERVIEW

Flexible and intuitive setup via PC through Ethernet

- Memorisation of 20 inspections
- 14 different controls
- 360° Contour Match for Professional models
- Logical operators: AND, OR, NOT, NAND, NOR, ecc.
- TURBO mode to double elaboration speed
- VSM compatibility
- Inspection & Identification functionalities together available on Professional models

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	n/a
Sensitivity adjustment	n/a

Application

Function Principle	SVS monitoring device
Description	3.5" LCD display / keyboard

Functions	SVS monitoring device
-----------	-----------------------

Outputs

Output type	n/a
-------------	-----

Response time	n/a
---------------	-----

Electrical data

Operating Voltage	n/a
-------------------	-----

Emission	n/a
----------	-----

Mechanical data

Dimensions	96x96x40
------------	----------

Housing Material	Plastic - ABS
------------------	---------------

Connections	M12 plug
-------------	----------

Storage temperature	- 25°C...+70°C
---------------------	----------------

Material	
----------	--

Generical Data

Dimensions	96x96x40
------------	----------

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail

date of printing

25/04/2026
04:43:39

info@datasensing.com