



SR23

953161020

SR23-2-IR-NH

HIGH EFFICIENCY FORK SENSOR FOR BOOKLET AND
MULTILAYER LABELS DETECTION

OVERVIEW

- Multilayer labels detection
- Up to 0,5 mm of minimum size labels/gap
- 5 mm slot width
- 50 mm slot depth
- Dynamic or static setting through single push-button
- 12 kHz switching frequency
- Compact and robust housing, IP65
- M8 connector or 2 m cable models
- PNP or NPN models

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	5mm
minimum detectable object	0,5mm
Sensitivity adjustment	Teach-in

Application

Function Principle	Fork for label detection
--------------------	--------------------------

Description	Slim case - fork slot 5x50 mm
Functions	Fork for label detection
Outputs	
Output type	NPN Don
Output Function	Don
Switching frequency	12kHz
Response time	40 μs
Electrical data	
Operating Voltage	10...30VDC
No-Load supply current	≤ 30mA
Output voltage drop	≤2V
Short-circuit protection	YES
Reverse Polarity Protection	Yes
Emission	LED Infrared
Interference to external light	according to EN 60947-5-2 : 2020
Impulsive Overvoltage Protection	Yes
Insulation resistance	>20 MΩ 500 Vdc, between electronics and housing
Contact resistance	500 Vac 1 min., between electronics and housing

Mechanical data

Dimensions	11x25x64
------------	----------

Material	
----------	--

Housing material	Metal - Zamak / PBT
------------------	---------------------

Connections	2m cable
-------------	----------

Active Head Material	PMMA
----------------------	------

Storage temperature	- 20°C...+70°C
---------------------	----------------

Depth slot detection	50,5mm
----------------------	--------

Test/Approvals

Approvals	CE cULus
-----------	----------

Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)
-----------------------	--

Generical Data

Dimensions	11x25x64
------------	----------

Operating Temperature	- 20°C...+ 55°C
-----------------------	-----------------

Mechanical Protection	IP65
-----------------------	------

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
10/08/2026
04:41:43

