SRF

95B020060

SRF-50-5-P

ULTIMATE PRECISION USING LED OR LASER EMISSIONS FOR HIGH RESOLUTION

OVERVIEW

- Visible red emission models
- High resolution LASER models
- Sensitivity adjustment trimmer and dark/light selectors
- Industrial metal housing with glass lenses

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	50mm
minimum detectable object	0,50mm
Sensitivity adjustment	Trimmer

Application

Function Principle	Fork for small object detection
Description	Slim case - fork slot 50x54 mm
Functions	Fork for small object detection

Outputs

Output type	PNP L/D selectable
Output Function	L/D selectable
Switching frequency	1,5kHz
Response time	0,33

Electrical data

Operating Voltage	10…30VDC
No-Load supply current	≤ 35mA
Load current	≤200mA
Output voltage drop	≤ 3V
LED indicators	yellow OUTPUT LED, green STABILITY LED
Emission	LED Red
Interference to external light	according to EN 60947-5-2 : 2020

Mechanical data

Dimensions	10x70x79
Housing Material	Metal - Gd-Zn / Glass
Connections	M8 plug 3pin
Storage temperature	- 20°C…+70°C

Material	

Test/Approvals

Approvals	CE cULus
Shocks and vibrations	0.5 mm amplitude, 10 … 55 Hz frequency, for every axis (EN60068-2-6)

Generical Data

Dimensions	10x70x79
Operating Temperature	- 10°C…+ 60°C (Without freeze)
Mechanical Protection	IP67

Datasensing S.r.l.
Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

date of printing
04/04/2026
07:34:15