



SRF

95B020120

SRF-120-5-N

**ULTIMATE PRECISION USING LED OR LASER EMISSIONS
FOR HIGH RESOLUTION**

OVERVIEW

- Visible red emission models
- High resolution LASER models
- Sensitivity adjustment trimmer and dark/light selectors
- Industrial metal housing with glass lenses

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	120mm
--------------------------	-------

minimum detectable object	0,80mm
---------------------------	--------

Sensitivity adjustment	Trimmer
------------------------	---------

Application

Function Principle	Fork for small object detection
--------------------	---------------------------------

Description	Slim case - fork slot 120x54 mm
-------------	---------------------------------

Functions	Fork for small object detection
-----------	---------------------------------

Outputs	
Output type	NPN L/D Selectable
Output Function	L/D Selectable
Switching frequency	1,5kHz
Response time	0,33
Electrical data	
Operating Voltage	10...30VDC
No-Load supply current	≤ 35mA
Load current	≤200mA
Output voltage drop	≤ 2,5V
LED indicators	yellow OUTPUT LED, green STABILITY LED
Emission	LED Red
Interference to external light	according to EN 60947-5-2 : 2020
Mechanical data	
Dimensions	10x140x84
Material	
Housing material	Metal - Gd-Zn / Glass
Connections	M8 plug 3pin

Storage temperature	- 20°C...+70°C
---------------------	----------------

Test/Approvals

Approvals	CE cULus
-----------	----------

Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)
-----------------------	--

Generical Data

Dimensions	10x140x84
------------	-----------

Operating Temperature	- 10°C...+ 60°C (Without freeze)
-----------------------	----------------------------------

Mechanical Protection	IP67
-----------------------	------

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
10/08/2026
02:37:05