



SRF

95B020140

SRF-L-50-5-P

**ULTIMATE PRECISION USING LED OR LASER EMISSIONS
FOR HIGH RESOLUTION**

OVERVIEW

- Visible red emission models
- High resolution LASER models
- Sensitivity adjustment trimmer and dark/light selectors
- Industrial metal housing with glass lenses

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	50mm
minimum detectable object	0,08mm
Sensitivity adjustment	Trimmer

Application

Function Principle	Fork for small object detection
Description	Slim case - fork slot 50x54 mm
Functions	Fork for small object detection

Outputs	
Output type	PNP L/D selectable
Output Function	L/D selectable
Switching frequency	5kHz
Response time	0,1
Electrical data	
Operating Voltage	10...30VDC
No-Load supply current	≤ 20mA
Load current	≤200mA
Output voltage drop	≤ 3V
LED indicators	yellow OUTPUT LED, green STABILITY LED
Emission	LASER Red
Interference to external light	according to EN 60947-5-2 : 2020
Mechanical data	
Dimensions	10x70x79
Material	
Housing material	Metal - Gd-Zn / Glass
Connections	M8 plug 3pin

Storage temperature	- 20°C...+70°C
---------------------	----------------

Test/Approvals

Approvals	CE cULus
-----------	----------

Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)
-----------------------	--

Generical Data

Dimensions	10x70x79
------------	----------

Operating Temperature	- 10°C...+ 60°C (Without freeze)
-----------------------	----------------------------------

Mechanical Protection	IP67
-----------------------	------

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
10/08/2026
01:36:56