

CF



CF/CA-M6-210

Optical fibre,Diff.,Axial,Plastic,2m
PLASTIC OPTICAL FIBRES

OVERVIEW

- Wide range of models: ultra slim for small object, long distances, spiral tube for handling
- Wide range of flexible fibre heads (with sleeve)
- Wide range of cutting fibre units
- P67 protection degree
- SSF – FS1 – FX3 – FX4 series connectable
- Approvals: CE

TECHNICAL FEATURES

Detection properties

Distance with SSF	80 mm
Distance with FS1	55 mm
Distance with FX3	200 mm
Distance with FX4	245 mm
Distance with F1R	160 mm
Distance with FY2	110 mm

Distance with FY3	215 mm
-------------------	--------

Application

Function Principle	Coaxial
Description	Plastic optical fibres
Optic position	Axial

Mechanical data

Operating temperature	-55°C....+70°C (posa fissa)
Fibre lengh (m)	2
Ø optical fibre core	1 mm
Head shape	M6
Optical fibre material	PE, plastic
Head material	stainless steel

Test/Approvals

Degree of protection	IP67
----------------------	------

Generical Data

Operating Temperature	-55°C....+70°C (posa fissa)
Mechanical Protection	IP67

**Datasensing
S.r.l.**

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
10/08/2026
01:07:37