

CF



CF/DR-M6-210

Optical fibre,Diff.,90°,Plastic,2m
PLASTIC OPTICAL FIBRES

OVERVIEW

- Wide range of models: ultra slim for small object, long distances, spiral tube for handling
- Wide range of flexible fibre heads (with sleeve)
- Wide range of cutting fibre units
- P67 protection degree
- SSF – FS1 – FX3 – FX4 series connectable
- Approvals: CE

TECHNICAL FEATURES

Detection properties

Distance with SSF	60 mm
Distance with FS1	45 mm
Distance with FX3	185 mm
Distance with FX4	220 mm
Distance with F1R	100 mm
Distance with FY2	60 mm

Distance with FY3	110 mm
-------------------	--------

Application

Function Principle	Diffusione diretta
Description	Plastic optical fibres
Optic position	90°

Mechanical data

Operating temperature	-55°C....+70°C (posa fissa)
Fibre lengh (m)	2
Ø optical fibre core	1 mm
Head shape	M6
Optical fibre material	PE, plastic
Head material	stainless steel

Test/Approvals

Degree of protection	IP67
----------------------	------

Generical Data

Operating Temperature	-55°C....+70°C (posa fissa)
Mechanical Protection	IP67

**Datasensing
S.r.l.**

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
10/08/2026
05:21:59