

CF



CF/TA-H2-210

Optical fibre,E+R Area,Axial,Plastic,2m
PLASTIC OPTICAL FIBRES

OVERVIEW

- Wide range of models: ultra slim for small object, long distances, spiral tube for handling
- Wide range of flexible fibre heads (with sleeve)
- Wide range of cutting fibre units
- P67 protection degree
- SSF – FS1 – FX3 – FX4 series connectable
- Approvals: CE

TECHNICAL FEATURES

Detection properties

Distance with SSF	430 mm
Distance with FS1	45 mm
Distance with FX3	730 mm
Distance with FX4	950 mm
Distance with F1R	510 mm
Distance with FY2	400 mm

Distance with FY3	430 mm
-------------------	--------

Application

Function Principle	Area (Emitter + Receiver)
Description	Plastic optical fibres
Optic position	Axial

Mechanical data

Operating temperature	-55°C....+70°C (posa fissa)
Fibre lengh (m)	2
Ø optical fibre core	1 mm
Head shape	19 x 6 x 25 mm
Optical fibre material	plastic
Head material	plastic

Test/Approvals

Degree of protection	IP67
----------------------	------

Generical Data

Operating Temperature	-55°C....+70°C (posa fissa)
Mechanical Protection	IP67

**Datasensing
S.r.l.**

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
10/08/2026
06:42:28