



CS & CAB

95A251270

CS-A1-02-G-05

THE RIGHT CONNECTION FOR YOUR PHOTOELECTRIC
SENSORS FOR INDUSTRIAL ENVIRONMENT 24VDC OR
10-30VDC POWER SUPPLY

OVERVIEW

- M8 and M12, axial or radial female connectors
- Standard length cables: 2, 3, 5, 7, 10, 15, 25 or 50m
- 3, 4, 5, 8 or 12 poles
- Shielded or unshielded models
- P.U.R. coated models for use in harsh environments
- P.V.C. coated models for standard use
- Standard M12 4 pole non-cabled connectors
- The cable jacket maybe marked 300V only as insulation voltage between wires, the operational voltage is 24Vdc or 10-30Vdc, less than 80 V required by CCC-China

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	n/a
Sensitivity adjustment	n/a

Application

Description	Straight female
Functions	Cable/connector

Outputs

Output type	n/a
Response time	n/a

Electrical data

Operating Voltage	10-30 VDC
Emission	n/a

Mechanical data

Dimensions	L=5m
Material	PVC (Grey)
Connections	M12 4-poles

Generical Data

Dimensions	L=5m
------------	------

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
13/06/2026
05:59:43