




CD

CD08/0A-050A5

Connect.M8-F,3 poles-5m,PUR,Axial

TECHNICAL FEATURES

Electrical data

Nominal current	4 A
Led	no
Wires	3
Rated impulse voltage	1,5 kV
Nominal voltage	Max. 60 V ac/dc

Mechanical data

Connections	With open ended wires
Tightening torque	0,4 Nm
Operating temperature	-5°C...+80°C (flexible installation) -20°C...+80°C (fixed installation)
Fibre lengh (m)	5
Head type	Axial
Plug	M8

Outer diameter	Ø 3,75 mm ±0,2mm
Jacket material	PUR
Wire isolation	PVC
Conductors section	0,25 mm2 (32 x 0,10 mm2)
Model	

Test/Approvals

Degree of protection	IP67
----------------------	------

Generical Data

Operating Temperature	-5°C...+80°C (flexible installation) -20°C...+80°C (fixed installation)
Mechanical Protection	IP67

CONNECTIONS

Eletrical diagram


BN/1

BU/3

BK/4

OTHERS

Dimensions



**Datasensing
S.r.l.**

Strada S.Caterina, 235
41122 Modena (MO)

**date of
printing**
10/08/2026
05:23:13

Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com