



# CD

## CD08/0A-050C1

Connect.M8-F,3 poles-5m,PVC,90°

## TECHNICAL FEATURES

### Electrical data

Nominal current	4 A
Led	no
Wires	3
Rated impulse voltage	0,8 kV
Nominal voltage	Max. 60 V ac/dc

### Mechanical data

Connections	With open ended wires
Tightening torque	0,4 Nm
Operating temperature	-10°C...+80°C (flexible installation) -25°C...+80°C (fixed installation)
Fibre length (m)	5

Head type	90°
Plug	M8
Outer diameter	Ø 4,5 mm ± 5%
Jacket material	PVC
Wire isolation	PVC
Conductors section	0,25 mm <sup>2</sup> (32 x 0,10 mm <sup>2</sup> )
Model	

#### Test/Approvals

Degree of protection	IP67
----------------------	------

#### Generical Data

Operating Temperature	-10°C...+80°C (flexible installation) -25°C...+80°C (fixed installation)
Mechanical Protection	IP67

## CONNECTIONS

Electrical diagram

BN/1  
\_\_\_\_\_

BU/3  
\_\_\_\_\_

BK/4  
\_\_\_\_\_

## OTHERS

Dimensions

Image:

### **Datasensing S.r.l.**

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail  
info@datasensing.com

**date of  
printing**  
05/04/2026  
16:41:30