



CD

CD08/0B-100A5US

Connect.M8-F,4 poles-10m,PUR,Axial

TECHNICAL FEATURES

Electrical data

Nominal current	4 A
Led	no
Wires	4
Rated impulse voltage	1,5 kV
Nominal voltage	Max. 30 V ac/dc

Mechanical data

Connections	With open ended wires
Tightening torque	0,4 Nm
Operating temperature	-25°C... +80°C (flexible installation)-25°C ... +80°C (fixed installation)
Fibre length (m)	10
Head type	Axial

Plug	M8
Outer diameter	Ø 4.1 mm ± 5%
Jacket material	PUR
Wire isolation	PP
Conductors section	0,25 mm2 (32 x 0,10 mm2)
Model	

Test/Approvals

Approvals	cCSAus
Degree of protection	IP67

Generical Data

Operating Temperature	-25°C... +80°C (flexible installation)-25°C ... +80°C (fixed installation)
Mechanical Protection	IP67


CONNECTIONS

Eletrical diagram

BN/1
WH/2
BU/3
BK/4

OTHERS

Dimensions



**Datasensing
S.r.l.**

Strada S.Caterina, 235
41122 Modena (MO)

**date of
printing**
10/08/2026
03:19:40

Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com