



CD

CL08/0A-00A

Connect.M8-F-Axial,3 p,Field attach.

TECHNICAL FEATURES

Application

Fixing	screw terminals
--------	-----------------

Electrical data

Rated current	a 40°C 4 A
---------------	------------

Led	no
-----	----

Wires	3
-------	---

Insulation resistance	$\geq 100 \text{ M}\Omega$
-----------------------	----------------------------

Contact resistance	$\leq 5 \text{ m}\Omega$
--------------------	--------------------------

Rated voltage	60 V (3 plugs) 30 V (4 plugs)
---------------	-------------------------------

Mechanical data

Connections	Field attachable
-------------	------------------

Tightening torque	0,2 Nm (M8 nut)
-------------------	-----------------

Operating temperature	-40 °C ... 85 °C
-----------------------	------------------

Head type	Axial
Plug	M8
Outer diameter	3,5 mm ... 5 mm
Stripping lenght of the sheath	12 mm
Wire isolation	$\geq 100\text{ M}\Omega$
Conductors section	0,14 mm ² ...0,5 mm ²
Model	Female

Test/Approvals


Degree of protection	IP67
----------------------	------

Generical Data

Operating Temperature	-40 °C ... 85 °C
Mechanical Protection	IP67

OTHERS

Dimensions



Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
10/08/2026
07:31:29