



US50

95ACC7820

ST-30SC
ULTRASONIC SENSOR

OVERVIEW

- Digital bipolar PNP/ NPN NO /NC configurable output model
- Digital and 0-10 V / 4-20 mA configurable analogue output model
- Operating range of 200 mm...8m
- Minimum resolution: 1 mm
- Analogue output Linearity: +/- 0.2% of span from 200 to 8000 mm; +/- 0.1% of span from 500 to 8000 mm (1 mm minimum)
- Minimum window size: 20mm
- Repeatability: 1 mm
- Hysteresis: 5 mm
- Response Time: 100 ms to 1600 ms
- DIP SWITCH selectable
- Access to bank of 8 DIP switches through sealed cover for superior user functionality
- Fast, easy-to-use REMOTE TEACH - Mode programming; no potentiometer adjustments
- Wide operating range of -20° to +70°C with compensation function
- Rugged encapsulated design for harsh environments
- Unique housing design allows for multiple mounting configurations
- Euro-style quick-disconnect fitting

TECHNICAL FEATURES

Detection properties

Nominal sensing distance

n/a

Sensitivity adjustment	n/a
------------------------	-----

Application

Description	Ø30 clamp with screws
Functions	US30-US50 mounting support

Outputs

Output type	n/a
Response time	n/a

Electrical data

Operating Voltage	n/a
Emission	n/a

Mechanical data

Dimensions	67x58x29
Connections	n/a
Material	Plastic

Generical Data

Dimensions	67x58x29
------------	----------

Fax 059 253973
E-mail
info@datasensing.com