



UK1

UK1C/G6-1EIOSY

Ultra.M18,PNP+4-20mA,M12 plug,Diffuse
M18 CYLINDRICAL DIRECT DIFFUSE &
RETRO-REFLECTIVE ULTRASONIC SENSOR UK1 WITH
TEACH-IN BUTTON

OVERVIEW

- Models with digital programmable output
- Models with current or voltage analogue outputs
- Adjustable Hysteresis function: model with programmable double digital outputs, specific for levels
- Working area adjusting (window teach or single point teach) by Teach-in button suitable for all models for a fast coming into work
- Multifunction LED indicator: output type, adjustment procedure, NO/NC selection and reverse analog output slope

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	900mm
--------------------------	-------

Thermal drift of Sr	±2%
---------------------	-----

Repeat Accuracy	0,50%
-----------------	-------

Sensitivity adjustment	Teach-in button
------------------------	-----------------

thermal compensation	
----------------------	--

Minimum sensing distance (blind	
---------------------------------	--

zone)	100mm
-------	-------

Application

Function Principle	Diffuse reflection
--------------------	--------------------

Outputs

Output type	IO-Link/PNP + 4...20mA
Output Function	NO/NC + positive/negative slope
Switching frequency	3Hz

Electrical data

Operating Voltage	10 - 30Vdc
No-Load supply current	≤50mA
Load current	100mA
Leakage current	10µA @ 30Vcc
Max ripple content	5%
LED indicators	green: echo - yellow: output
Short-circuit protection	Yes
Reverse Polarity Protection	Yes
Impulsive Overvoltage Protection	Yes

Mechanical data

Dimensions	M18 x 1 / L = 91,6mm
------------	----------------------

Housing material	stainless steel AISI 316L
Weight	100g
Connections	M12 Plug
Active Head Material	10° ± 2°
Tightening torque	1Nm
Operating temperature	- 20°C...+ 70°C
Storage temperature	- 35°C...+ 80° C without freeze
Diameter/Dimension	M18

Test/Approvals

Approvals	CE cULus
EMC compatibility	IEC 60947-5-2
Shocks and vibrations	IEC EN60947-5-2 / 7.4
Degree of protection	IP67

Accessories


Supplied Accessories	2 x M18 x 1 nuts, 2 Ø 18 washers
----------------------	----------------------------------

Generical Data

Dimensions	M18 x 1 / L = 91,6mm
Operating Temperature	- 20°C...+ 70°C

OTHERS

Dimensions



1 Teach-in

2 LED

**Datasensing
S.r.l.**

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
10/08/2026
02:16:55