

US30



95B040110

US30-PR-5-N23-OH
ULTRASONIC SENSOR

OVERVIEW

- Digital bipolar PNP/ NPN NO /NC configurable output model
- Digital and 0-10 V / 4-20 mA configurable analogue output model
- Operating range of 200 mm...8m
- Minimum resolution: 1 mm
- Analogue output Linearity: +/- 0.2% of span from 200 to 8000 mm; +/- 0.1% of span from 500 to 8000 mm (1 mm minimum)
- Minimum window size: 20mm
- Repeatability: 1 mm
- Hysteresis: 5 mm
- Response Time: 100 ms to 1600 ms
- DIP SWITCH selectable
- Access to bank of 8 DIP switches through sealed cover for superior user functionality
- Fast, easy-to-use REMOTE TEACH - Mode programming; no potentiometer adjustments
- Wide operating range of -20° to +70°C with compensation function
- Rugged encapsulated design for harsh environments
- Unique housing design allows for multiple mounting configurations
- Euro-style quick-disconnect fitting

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	2 m
--------------------------	-----

Sensitivity adjustment

Teach-in

Application

Description

M30 tubular - lateral emission

Functions

Object detection/distance meas.

Outputs

Output type

NPN / PNP

Response time

100,000

Electrical data

Operating Voltage

10-30 VDC

Emission

174kHz

Mechanical data

Dimensions

Ø30x45

Material

Plastic - PBT

Connections

M12

Generical Data

Dimensions

Ø30x45

Datasensing
S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411

date of
printing

10/08/2026
02:20:00

Fax 059 253973
E-mail
info@datasensing.com