



DS4 Standard

957650114

DS4-25-1800-S08-JZ

DETECTION AND MEASUREMENT AREA SENSOR

OVERVIEW

Versatile area sensors for detecting and measuring in various industrial applications. Conveniently configured using IO-Link and wirelessly programmable through AppGUI for detailed parameter adjustments and advanced setups.



TECHNICAL FEATURES

Detection properties

Nominal sensing distance	0.2...13 m
Beams space	25 mm
controlled height	1800 mm
number of rays	72
Sensitivity adjustment	remote teach, IO-Link, AppGUI
Detection capability	25 mm

Features and performances

Detection capability	0
----------------------	---

Application

Description	DS4-25-1800-S08-JZ 25mm H=1800mm IOL
-------------	--------------------------------------

Outputs

Output type	PNP or NPN or Push-Pull , 0...10 V, 4..20 mA, IO-Link, RS485
-------------	--

Output Function	Light array for detection and measurement
-----------------	---

Electrical data

Operating Voltage	19.2...28.8 Vdc
-------------------	-----------------

No-Load supply current	360 mA (emitter and receiver)
------------------------	-------------------------------

Leakage current	100 mA
-----------------	--------

Output voltage drop	2.5 V @ IL=100 mA
---------------------	-------------------

Time delay before availability	3.16 s
--------------------------------	--------

Short-circuit protection	Yes
--------------------------	-----

Reverse Polarity Protection	Yes
-----------------------------	-----

Emission	Infrared (850 nm) Emitter + Receiver
----------	--------------------------------------

Impulsive Overvoltage Protection	Yes
----------------------------------	-----

Protection against inductive loads	Yes
------------------------------------	-----

Mechanical data

Material	Aluminium / PBT
----------	-----------------

Housing material	Aluminium
------------------	-----------

Optic window material	PMMA
-----------------------	------

Weight	1.4 Kg/m (single bar, without package)
--------	--

Connections	M12 5 poles + 200 mm length cable TPU (TX), M12 8 poles + 200 mm length cable TPU (RX)
Active Head Material	PMMA
Storage temperature	-30...+70 °C
Humidity	15...95 % (without freeze)
Test/Approvals	
Shocks and vibrations	10 mm / 3g, 5 ... 150 Hz frequency, (EN 60068-2-6 / Class 3M7 IEC TR 60721-4-3); 25g x 6 ms x 600 (EN 60068-2-27 / Class 3M7 IEC TR 60721-4-3)
Accessories	
Supplied Accessories	Fixing brackets
Generical Data	
Dimensions	35 x 40 x 1809 mm
Operating Temperature	-30...+50°C (without freeze)
Mechanical Protection	IP65 IP67
HMI/UI	
LED indicators	TX: Green (Power ON), Yellow (Emission range) Red (Test, failure, Firmware ongoing update), Blue (Emission range, Firmware update completed) RX: Green (Power ON), Yellow (Status output, Connection and teach-in active) Red (Hardware Errors, Invalid con

Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com