



S3N

95B010166

S3N-PR-5-C12-NL
MINIATURE PHOTOELECTRIC SENSOR

OVERVIEW

- Bright LED RED/IR and Safe Laser emission models
- Smart BGS and clear detection functions
- Single, Double trimmer & Push Button models
- Long distance detection models
- Very fast and very precise RGB Contrast sensor
- Cable, M8 connector, Pigtail M8 and M12 connection
- Rugged IP67 Plastic miniature case
- IO-Link with extended Smart Tasks

TECHNICAL FEATURES

Detection properties

Nominal sensing distance	1 m
Sensitivity adjustment	1 turn trimmer
Minimum sensing distance (blind zone)	0 mm

Application

Function Principle	Diffused
--------------------	----------

Notes	white target Kodak 90% 400 x 400mm
Optic position	Radial 90°
Functions	Diffused

Outputs

Output type	NPN Light
Output Function	Light output
Switching frequency	500 Hz
Response time	1 ms

Electrical data

Operating Voltage	10...30VDC
No-Load supply current	≤ 35mA
Load current	≤100mA
Leakage current	≤ 300 µA
Output voltage drop	≤2V@Iload=100mA
Max ripple content	≤10%
LED indicators	yellow OUTPUT LED, green STABILITY LED
Short-circuit protection	Yes
Reverse Polarity Protection	Yes

Emission	850 nm Infrared LED
Interference to external light	according to EN 60947-5-2 : 2020
Impulsive Overvoltage Protection	Yes
Insulation resistance	>20 MΩ 500 Vdc, between electronics and housing
Contact resistance	500 Vac 1 min., between electronics and housing

Mechanical data

Dimensions	11x31x19 mm
Housing material	Plastic Polymer Fiber Glass reinforced
Active Head Material	PMMA
Operating temperature	-25°C ... 55°C
Storage temperature	- 25°C...+70°C
Plug connector material	Metal
shaft material	POM, PMMA
Diameter/Dimension	Cubic
Mechanical protection	IP67

Test/Approvals

Approvals	CE cULus
EMC compatibility	EN 60947-5-2
Shocks and vibrations	0.5 mm amplitude, 10 ... 55 Hz frequency, for every axis (EN60068-2-6)

Generical Data

Operating Temperature	-25°C ... 55°C
-----------------------	----------------

Mechanical Protection	IP67
-----------------------	------

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail
info@datasensing.com

**date of
printing**
10/08/2026
03:01:50